



# YY-CDD-CB30

插地灯

## 材质结构 / Material structure

- 材 质: ADC12压铸铝, 独特设计的散热器具具有: 传导快, 散热好, 保证光源光衰小, 寿命更长
- 表面处理: 静电喷塑, 可定制颜色
- 光学部分: COB光源, 遮光罩防眩设计, 光斑均匀, 出光效率更高
- 密封结构: 灌胶防水, 防护等级IP65
- 安装方式: 铝材地插, 可旋转结构, 安装简单, 使用范围广, 对施工要求不高
- 连接方式: 橡胶线伸出连接
- 可 选 项: 可内置防眩光网, 遮光罩可选装

Material: ADC12 die cast aluminum, uniquely designed heat sink with fast conduction, good heat dissipation, ensuring minimal light attenuation and longer lifespan of the light source

Surface treatment: electrostatic spraying, customizable colors

Optical part: COB light source, anti glare design of light shield, uniform light spot, higher light output efficiency


Sealing structure: Glue filled waterproof, protection level IP65

Installation method: Aluminum ground plug, rotatable structure design, easy installation, wide range of use, low construction requirements

Connection method: Rubber wire extension connection

Optional: Built in anti glare mesh, optional light shield

## 配光曲线 / Custom



## 产品参数 / Product parameters

产品型号	YY-CDD-CB30	Product Model	YY-CDD-CB30
光源品牌	OSRAM/CREE	LED Brand	OSRAM/CREE
控制方式	开关控制	Control Mode	ON/OFF
可选功率	3W-30W	Power	3W-30W
输入电压	AC85-268V /DC24V	Voltage	AC85-268V /DC24V
发光颜色	单色	Color	2000K-6500K/R/G/B
显色性	Ra > 80	CRI	Ra > 80
平均寿命	50000H	Service Life	50000H
材 质	铝材+钢化玻璃	Material	Aluminum+Tempered glass
防护等级	IP65	Ingress Protection	IP65

## 产品尺寸 / Product size

型号/Model	功率/Power	色温/K	Unit:mm(±2mm)	
			直径/φ	宽/W
YY-CDD-CB03	3W	1800K-3600K	42	112
YY-CDD-CB07	7W	1800K-3600K	50	140
YY-CDD-CB12	12W	1800K-3600K	58	175
YY-CDD-CB18	18W	1800K-3600K	80	170
YY-CDD-CB30	30W	1800K-3600K	100	150



## 灯具颜色 / Custom



## 发光颜色 / Custom

