

# YY-TGD-LP600

投光灯




## 材质结构 / Material structure

- 材 质: ADC12压铸铝, 独特设计的散热器具有: 传热快, 散热好, 保证光源光衰小、寿命更长
- 表面处理: 静电喷塑, 可定制颜色
- 光学部分: 二次光学透镜配光, 多角度可选, 钢化玻璃防护, 防眩设计, 光斑均匀, 出光效率更高
- 密封结构: 灌胶防水, 防护等级IP66
- 安装方式: 钣金支架平面安装, 可旋转结构, 安装简易, 使用范围广, 对施工要求不高
- 连接方式: 工业耦合器手挽手连接或橡胶线伸出连接
- 可 选 项: 可内置防眩光网, 遮光罩可选装

Material: ADC12 die cast aluminum, uniquely designed heat sink with fast conduction, good heat dissipation, ensuring minimal light attenuation and longer lifespan of the light source  
 Surface treatment: electrostatic spraying, customizable colors  
 Optical part: Secondary optical lens distribution, multiple angle options, tempered glass protection, anti glare design, uniform light spot, higher light output efficiency  
 Sealing structure: Glue filled waterproof, protection level IP66  
 Installation method: Sheet metal bracket flat installation, rotatable structural design, easy installation, wide range of use, low construction requirements  
 Connection method: Industrial coupler arm in arm connection or rubber wire extension connection  
 Optional: Built in anti glare mesh, optional light shield

## 配光曲线 / Custom



## 产品参数 / Product parameters

产品型号 YY-TGD-LP600  
 光源品牌 OSRAM/CREE  
 控制方式 单色静态/DMX512  
 可选功率 100W-600W  
 输入电压 AC85-268V  
 发光颜色 单色/RGBW  
 显色性 Ra > 80  
 平均寿命 50000H  
 材 质 铝材+钢化玻璃  
 防护等级 IP66

Product Model YY-TGD-LP600  
 LED Brand OSRAM/CREE  
 Control Mode ON/OFF /DMX512  
 Power 100W-600W  
 Voltage AC85-268V  
 Color 单色/RGBW  
 CRI Ra > 80  
 Service Life 50000H  
 Material Aluminum+tempered glass  
 Ingress Protection IP66

## 可定制 / Custom



## 产品尺寸 / Product size

型号/Model	功率/Power	色温/C	长/L	Unit:mm(±2mm)	
				高/H	宽/W
YY-TGD-LP100	100W/150W	1800K-3600K/RGBW	404	320	124
YY-TGD-LP200	200W	1800K-3600K/RGBW	490	350	130
YY-TGD-LP300	300W	1800K-3600K/RGBW	645	355	140
YY-TGD-LP400	200W×2	1800K-3600K/RGBW	590	553	240
YY-TGD-LP600	300W×2	1800K-3600K/RGBW	703	553	235

